

DAHLVIA 9119 Conformable Release Film

			-	60	
- 1	es		m	м	n-
- 7/	1001	71	10		 ше

A multilayer, highly conformable release sheet / pressure intensifier all in one designed especially for use in flexible circuit lamination applications.

Suggested Applications:

A conformable film with integral release surfaces on two sides. Designed to offer maximum conformability to block resin flow in FPC lamination applications.

Technical Data:

Maximum Use Temperature: 390°F / 199°C

Thickness: .0047"/ .120 mm, .0065" / .163 mm

Elongation: MD 140% Color: Clear

Features / Benefits:

Utilizing a unique combination of PMP outer layer release surfaces and a proprietary conformable inner layer, DAHLVIA 9119 softens and conforms to the substrate creating a dam against unwanted acrylic / epoxy intrusion while providing for easy release from many surfaces.

Related Airtech Products:

Dahlpad One, Tri-Pad, Si-Pad press pads, Dahlar high temperature release films

As the conditions or methods of use, including storage, are beyond our control, Airtech International, Inc. does not assume any responsibility for the performance of this material for any particular use. The material is sold "as is". Airtech International, Inc. disclaims, and buyer waives, any and all implied warranties, including without limitation the warranties of merchantability and of fitness for a particular use.

Distributed By:							